

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION

PRODUCT: PNEUMATIKOEL 32
PRODUCT #: G-EAG0639
PHSD #: 41-4020000
REVISION: 27 JANUARY 1998
SUPERSEDES: 21 JANUARY 1997

ESSO A.G.
Kapstadtring 2
22297 Hamburg

Medical Emergency:
040-7671 1320/1321
If unreachable:
040-6393 3555/3666
Other:
040-63930

REVISION CHANGES:
Change of section 2.

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients present at or above 0.1 wt% (classified as toxic or very toxic) or 1 wt% (classified as harmful, irritant or corrosive).

HAZARDOUS INGREDIENT	APPROXIMATE CONCENTRATION
Xi Oleyl cetyl alcohol with 2 EO R 38 Irritating to skin	2,0 Masse %

3. HAZARD IDENTIFICATION

This product consists of highly refined base oils with additives.

It is of low oral and dermal toxicity and under normal conditions of use should present no significant health hazards. However, in common with most mineral oils, prolonged and repeated skin contact may cause dermatitis.

Handling precautions should be strictly observed.

4. FIRST AID

INHALATION:

At ambient/normal handling temperatures, inhalation of vapors is normally not a problem. If overexposed to oil mist, remove from further exposure. Administer artificial respiration if breathing is irregular or has stopped. Get prompt medical attention.

PRODUCT: PNEUMATIKOEL 32

E S S O A.G.

4. FIRST AID (Continued)**SKIN CONTACT:**

No adverse effects due to skin contact are expected.

EYE CONTACT:

Rinse immediately with plenty of water until irritation subsides.
If irritation persists, obtain medical advice.

INGESTION:

If swallowed, keep at rest and call a physician. Do not induce vomiting unless directed to do so by a medical professional.

5. FIRE-FIGHTING MEASURES**EXTINGUISHING MEDIA:**

Foam, dry chemical powder, carbon dioxide.

FIRE AND EXPLOSION HAZARDS:

Combustible material, low hazard. The product can form flammable mixtures or can burn only on heating above the flash point. However, minor contamination by hydrocarbons of higher volatility may increase the hazard.

SPECIAL FIRE-FIGHTING PROCEDURES:

Water fog or spray, to cool fire-exposed surfaces (e.g. containers) and to protect personnel, should only be used by personnel trained in fire fighting.

Cut off "fuel"; depending on circumstances, either allow the fire to burn out under controlled conditions or use foam or dry chemical powder to extinguish the fire.

Respiratory and eye protection required for fire fighting personnel exposed to fumes or smoke.

HAZARDOUS COMBUSTION PRODUCTS:

Smoke, carbon monoxide, carbon dioxide and oxides of sulphur and phosphorus.

Various metal oxides

PRODUCT: PNEUMATIKOEL 32

E S S O A.G.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: See Section 8.

LAND SPILL:

Shut off source taking normal safety precautions. Prevent liquid from entering sewers, water courses or low lying areas; advise the relevant authorities if it has, or if it contaminates soil/vegetation. Take measures to minimise the effects on ground water.

Recover by skimming or pumping using explosion-proof equipment, or contain spilled liquid with booms, sand, or other suitable absorbent and remove mechanically into containers.

If necessary, dispose of adsorbed residues as directed in Section 13.

De-water sludge and, if necessary, dispose as directed in Section 13.

WATER SPILL:

Confine the spill immediately with booms. Warn other shipping. Notify port and other relevant authorities.

7. HANDLING AND STORAGE

Store the product in cool, well ventilated surroundings, well away from sources of ignition.

Provide suitable mechanical equipment for the safe handling of drums and heavy packages.

Electrical equipment and fittings must comply with local regulations regarding fire prevention with this class of product.

LOAD/UNLOAD TEMPERATURE deg. C: Ambient to max. 60 C

STORAGE TEMPERATURE deg. C: Ambient to max. 50 C

SPECIAL PRECAUTIONS:

Keep containers closed when not in use.

Prevent small spills and leakages to avoid slip hazard.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

OCCUPATIONAL EXPOSURE LIMIT:

5 mg/m³ for oil mists (TWA, 8h - workday) recommended based upon the ACGIH TLV (Analysis according to US NIOSH Method 5026, NIOSH Manual of Analytical Methods, 3rd Ed.).

PRODUCT: PNEUMATIKOEL 32

E S S O A.G.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION (Continued)**PERSONAL PROTECTION:**

In open systems where contact is likely, wear safety goggles, chemical-resistant overalls, and chemically impervious gloves.

Where only incidental contact is likely, wear safety glasses with side shields. No other special precautions are necessary provided skin/eye contact is avoided.

When concentrations in air may exceed the occupational exposure limit, and where engineering, work practices, or other means of exposure reduction are not adequate, approved respirators may be required.

9. PHYSICAL AND CHEMICAL PROPERTIES**APPEARANCE / ODOUR:**

Clear brown liquid.

DENSITY, g/ml: 0.9 at 15 deg. C DIN 51 757

BOILING RANGE: Data not available.

VISCOSITY, mm²/s: 30.3 at 40 deg. C DIN 51 562

VAPOUR DENSITY AT 1 BAR (Air=1): Heavier than air.

EVAPORATION RATE (n-butyl acetate=1): Non-volatile.

SOLUBILITY IN WATER: Emulsifies.

pH: Not Applicable.

FLASH POINT: 186 deg. C METHOD: COC DIN ISO 2592

FLAMMABILITY LIMITS IN AIR, % BY VOL:

LEL: 0.6 UEL: 6.5 (approx.)

AUTOIGNITION TEMPERATURE: Data not available.

PARTITION COEFFICIENT n-octanol/water: Data not available.

PRODUCT: PNEUMATIKOEL 32

E S S O A.G.

10. STABILITY AND REACTIVITY**STABILITY (THERMAL, LIGHT, ETC):** Stable**CONDITIONS TO AVOID:**

Keep away from heat sources, open flames and other sources of ignition.

INCOMPATIBLE MATERIALS:

Avoid contact with strong oxidants such as liquid chlorine and concentrated oxygen.

HAZARDOUS DECOMPOSITION PRODUCTS:

Smoke, and carbon monoxide may be formed in the event of incomplete combustion.

Product does not decompose at ambient temperature.

11. TOXICOLOGICAL INFORMATION**EFFECTS OF OVER EXPOSURE:****INHALATION:**

Negligible hazard at ambient/normal handling temperatures.

Elevated temperatures or mechanical action may form vapours, mists, or fumes which may be irritating to the eyes, nose, throat, and lungs.

Avoid breathing vapours, mists, or fumes.

SKIN CONTACT:

Low order of acute toxicity.

Prolonged or repeated contact may lead to mild skin irritation.

EYE CONTACT:

Slightly irritating, but does not injure eye tissue.

INGESTION:

Low order of acute/systemic toxicity.

PRODUCT: PNEUMATIKOEL 32

E S S O A.G.

11. TOXICOLOGICAL INFORMATION (Continued)**CHRONIC:**

Contains lubricating oil base stocks. Base oils of similar composition and refining history have exhibited no carcinogenic activity in laboratory animals.

TOXICITY DATA:**ACUTE:**

No test data are available for the complete formulated product. The potential health hazards described were therefore derived from what is generally known of the toxicity of the base oils and the additives, taking into account the concentrations at which they are present. The general effects of mineral oils of this type are well known and are described in numerous publications including CONCAWE Report 5/87 "Health Aspects of Lubricants".

CHRONIC:

Although there is no specific test data on the base oil components, the base oil would not be expected to exhibit carcinogenic potential based upon what is known of the toxicity of base oils in general.

12. ECOLOGICAL INFORMATION

In the absence of specific environmental data for this product, this assessment is based on information for general hydrocarbon components found in lubricant mineral oils. Lubricant mineral oils, immediately following a release into the environment, will remain largely on the soil surface, and in water, will remain largely on the water surface. Based on chemical/physical information from the literature for this product category, no harmful effects to terrestrial or aquatic habitats would be expected. This product is expected to be resistant to biodegradation and to persist in the environment. This product may contain additives for which no environmental data is available. Hence, the above assessment concerns the base oil(s) only.

13. DISPOSAL CONSIDERATIONS

Collect and dispose of waste product at an authorised disposal facility, in conformance with national and local regulations, and in accordance with EEC Directives on the disposal of waste oil.

PRODUCT: PNEUMATIKOEL 32

E S S O A.G.

14. TRANSPORT INFORMATION**USUAL SHIPPING CONTAINERS:**

Rail cars, tank trucks, drums.

TRANSPORT TEMPERATURE deg. C: Ambient to max. 50 C

15. REGULATORY INFORMATION**EC DANGEROUS SUBSTANCES/PREPARATIONS CLASSIFICATION:**

Not regulated

Refer to your national legislation implementing the EC Directive 91/155/EC

16. OTHER INFORMATION**PRODUCT TYPE / USES:**

Lubricating oil for pneumatic tools.

SOURCE OF KEY DATA:

The recommendations presented in this Material Safety Data Sheet were compiled from actual test data (when available), comparison with similar products, component information from suppliers and from recognised codes of good practice.

The information and recommendations contained herein are, to the best of Exxon's knowledge and belief, accurate and reliable as of the date issued, but are offered without guarantee or warranty. They relate to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Conditions of use of the material are under the control of the user; therefore, it is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use.